



# READYGO!



**Meexe ReadyGo!** is a highly decorative continuous coating for professionals.

**Meexe ReadyGo!** is a ready-to-use, flexible and resistant microcement. It can be applied to virtually any surface as long as it is level and consolidated, allowing any room to be renovated in both vertical and horizontal planes. Available in four granulometries.

## PROPERTIES

- Continuous seamless coating (always respect the expansion joints).
- Can be applied on almost any type of substrate: concrete, cements, ceramic, plaster, plasterboard, etc.
- Excellent workability.
- High adherence to the substrate.
- Does not yellow.
- Applicable in interiors and exteriors.
- Do not use mesh.
- Do not apply thick coat.
- Do not apply fresh on fresh.
- Available in 16 colours and 4 granulometries.

## CONSUMPTION

It will depend on the granulometry of the product.

For floors:

- **Meexe ReadyGo! 04** (0,5 mm): 1,3 Kg/m<sup>2</sup>
- **Meexe ReadyGo! 02** (0,250 mm): 0,450 Kg/m<sup>2</sup>

For walls:

- **Meexe ReadyGo! 03** (0,35 mm): 0,9 Kg/m<sup>2</sup>
- **Meexe ReadyGo! 01** (0,125 mm): 0,250 Kg/m<sup>2</sup>

## TECHNICAL DATA

### Meexe ReadyGo! 04 FLOORS\*

<b>Appearance</b>	Paste
<b>Grain size</b>	0,5 mm
<b>Density</b>	1,67 g/cm <sup>3</sup>
<b>Max. thickness per layer</b>	1 mm
<b>Abrasion Taber (CS17, 1000g, 1000c)</b>	66 mg
<b>Shore D hardness</b>	66

### Meexe ReadyGo! 02 WALLS\*

<b>Appearance</b>	Paste
<b>Grain size</b>	0,250 mm
<b>Density</b>	1,61 g/cm <sup>3</sup>
<b>Max. thickness per layer</b>	0,5 mm
<b>Abrasion Taber (CS17, 1000g, 1000c)</b>	66 mg
<b>Shore D hardness</b>	66

### Meexe ReadyGo! 03 WALLS\*

<b>Appearance</b>	Paste
<b>Grain size</b>	0,35 mm
<b>Density</b>	1,65 g/cm <sup>3</sup>
<b>Max. thickness per layer</b>	0,8 mm
<b>Abrasion Taber (CS17, 1000g, 1000c)</b>	42 mg
<b>Shore D hardness</b>	45

### PREPARATION OF THE SUBSTRATE

All surfaces must be level and consolidated. It is necessary to clean and dry the surface to be coated. It must be free of dust, grease, soaps, paint in poor condition, etc. If the substrate is damp, it must be pre-treated with **Meexe Cover**.

\* In tiles and other coverings with joints, it will be necessary to cover these joints beforehand with **Meexe Primer** and allow to dry for a minimum of 24 hours before applying the primer. On absorbent substrates such as concrete, plasterboard or lime, always use **Meexe Primer 100** as a primer.

On low or non-absorbent substrates such as terrazzo, marble or tiles, use **Meexe Primer 200**. Both primers must dry for a minimum of 30 minutes and a maximum of 2 hours.

Depending on the ambient temperature of the working space it is recommended to heat the area to an ideal temperature (20 - 22°C) for the application work. This will favour a quick drying of the product.

\* See STEP BY STEP

### APPLICATION ON FLOORS

Once the substrate has been correctly prepared, the following steps must be carried out.

**STEP 1.** Application of **Meexe ReadyGo! 04** (2 coats):

1. Before starting the application, it is necessary to homogenise **Meexe ReadyGo! 04** with the help of a mechanical stirrer or manually, vigorously. If you want to pigment, pour and homogenise.
2. Apply the product using a steel trowel in 2 coats of 1 mm maximum each. Allow to dry between coats 4 - 8h. It is necessary to sand each of the coats with 40 grit sandpaper.

**STEP 2.** **Meexe ReadyGo! 02** (1 coat):

1. Before starting the application of the product, it is necessary to homogenise the **Meexe ReadyGo! 02** with the help of a mechanical stirrer in a manual way. If pigmentation is desired, pour and homogenise.
2. Apply the product using a steel trowel in 1 very thin layer of max. 0,5 mm. The drying time of this layer is approximately 4 - 8 hours.
3. It is necessary to sand each of the coats with 120 to 220 grit sandpaper.

**STEP 3.** Sealing with **Meexe Sealant Go!** (3 - 4 coats):

1. Apply the product using a roller in 3 - 4 coats\* allowing 3h to dry between coats.
2. It is necessary to sand only the first coat with 400 grit sandpaper.

\*For damp and high traffic areas apply 4 coats.

### Meexe ReadyGo! 01 WALLS\*

<b>Appearance</b>	Paste
<b>Grain size</b>	0,125 mm
<b>Density</b>	1,63 g/cm <sup>3</sup>
<b>Max. thickness per layer</b>	0,3 mm
<b>Abrasion Taber (CS17, 1000g, 1000c)</b>	42 mg
<b>Shore D hardness</b>	45

### APPLICATION ON WALLS

Once the substrate has been correctly prepared, the following steps must be carried out.

**STEP 1.** Application of **Meexe ReadyGo! 03** (2 coats):

1. Before starting the application, it is necessary to homogenise **Meexe ReadyGo! 03** with the help of a mechanical stirrer or manually, vigorously. If you want to pigment, pour and homogenise.
2. Apply the product using a steel trowel in 2 coats of 1 mm maximum each. Allow to dry between coats 4 - 8h.
3. It is necessary to sand each of the coats with 40 grit sandpaper.

**STEP 2.** Application of **Meexe ReadyGo! 01** (1 coat):

1. Before starting the application of the product, it is necessary to homogenise the **Meexe ReadyGo! 01** with the help of a mechanical stirrer in a manual way. If pigmentation is desired, pour and homogenise.
2. Apply the product using a steel trowel in 1 very thin layer of max. 0,5 mm. The drying time of this layer is approximately 4 - 8 hours.
3. It is necessary to sand each of the coats with 120 to 220 grit sandpaper.

**STEP 3.** Sealed with **Meexe Sealant Go!** (3 - 4 coats):

1. Apply the product using a roller in 3 - 4 coats\* allowing 3h to dry between coats.
2. It is necessary to sand only the first coat with 400 grit sandpaper.

\*For damp and high traffic areas apply 4 coats.

### SPECIAL PRECAUTIONS

In case of contact with eyes, rinse with plenty of water for 15 minutes. In case of contact with skin wash with soap and water. Do not swallow. If swallowed do not induce vomiting and seek medical attention immediately.

**The following measures are recommended:**

- Good ventilation
- Protective goggles to prevent splashing.
- Rubber gloves

Empty containers should be disposed of in accordance with legal regulations. To prevent the product from drying out or thickening, close the lid after each use.

Keep out of reach of children.

## STEP BY STEP

	For FLOORS	For WALLS
PREPARING THE SUBSTRATE	1. On tiles, fill the joints with <b>Meexe Jointer</b> <ul style="list-style-type: none"> <li>• 24 hours</li> <li>• Grit sandpaper 40</li> </ul>	1. On tiles, fill the joints with <b>Meexe Jointer</b> <ul style="list-style-type: none"> <li>• 24 hours</li> <li>• Grit sandpaper 40</li> </ul>
	2. <b>Meexe Primer 200, Meexe Primer 100</b> <ul style="list-style-type: none"> <li>• 30 minutes / max. 2 hours</li> <li>• 1 coat</li> </ul>	2. <b>Meexe Primer 200, Meexe Primer 100</b> <ul style="list-style-type: none"> <li>• 30 minutes / max. 2 hours</li> <li>• 1 coat</li> </ul>
STEP 1	3. <b>Meexe ReadyGo! 04</b> <ul style="list-style-type: none"> <li>• Apply by trowel 1 pigmented coat</li> <li>• 4 - 8 hours</li> <li>• Grit sandpaper 40</li> </ul>	3. <b>Meexe ReadyGo! 04</b> <ul style="list-style-type: none"> <li>• Apply by trowel 1 pigmented coat</li> <li>• 4 - 8 hours</li> <li>• Grit sandpaper 40</li> </ul>
	4. <b>Meexe ReadyGo! 04</b> <ul style="list-style-type: none"> <li>• Apply by trowel 1 pigmented coat</li> <li>• 4 - 8 hours</li> <li>• Grit sandpaper 40</li> </ul>	4. <b>Meexe ReadyGo! 04</b> <ul style="list-style-type: none"> <li>• Apply by trowel 1 pigmented coat</li> <li>• 4 - 8 hours</li> <li>• Grit sandpaper 40</li> </ul>
STEP 2	5. <b>Meexe ReadyGo! 02</b> <ul style="list-style-type: none"> <li>• Aplicar mediante llana 1 capa pigmentada</li> <li>• 4 - 8 horas</li> <li>• Lija grano 120 / 220*1</li> </ul>	5. <b>Meexe ReadyGo! 02</b> <ul style="list-style-type: none"> <li>• Aplicar mediante llana 1 capa pigmentada</li> <li>• 4 - 8 horas</li> <li>• Lija grano 120 / 220*1</li> </ul>
<b>ANTES DEL PASO 3. SECADO 24 HORAS</b>		
STEP 3	6. <b>Meexe ReadyGo!</b> <ul style="list-style-type: none"> <li>• Lija grano 400 (sólo 1ª capa)</li> <li>• 3 - 4 capas*2 (cada 3h)</li> <li>*2 Para zonas húmedas y de alto tránsito aplicar 4 capas.</li> </ul>	6. <b>Meexe ReadyGo!</b> <ul style="list-style-type: none"> <li>• Lija grano 400 (sólo 1ª capa)</li> <li>• 3 - 4 capas*2 (cada 3h)</li> <li>*2 Para zonas húmedas y de alto tránsito aplicar 4 capas.</li> </ul>

Product	Consumption	Product	Consumption
<b>Meexe Primer 200</b>	0,09 L/m <sup>2</sup>	<b>Meexe Primer 200</b>	0,09 L/m <sup>2</sup>
<b>Meexe Primer 100</b>	0,10 L/m <sup>2</sup>	<b>Meexe Primer 100</b>	0,10 L/m <sup>2</sup>
<b>Meexe ReadyGo! 04</b>	1,300 Kg/m <sup>2</sup> (1 capa)	<b>Meexe ReadyGo! 03</b>	0,900 Kg/m <sup>2</sup> (1capa )
<b>Meexe ReadyGo! 02</b>	0,450 Kg/m <sup>2</sup> (1 capa)	<b>Meexe ReadyGo! 01</b>	0,250 Kg/m <sup>2</sup> (1capa)
<b>Meexe Sealant Go!</b>	0,2 - 0,25 L/m <sup>2</sup> ( 3 - 4 capas )	<b>Meexe Sealant Go!</b>	0,2 - 0,25 L/m <sup>2</sup> ( 3 - 4 capas )

Detailed information about the products can be found in the Technical Data Sheets.  
\*120: Machine sanding / 220: Hand sanding

## PACKAGING

It comes in buckets of 17,6 y 17 Kg.

## TOOL CLEANING

Tools should be washed with water immediately after use. Once hardened, the material may only be removed by mechanical means.

## STORAGE CONDITIONS

The product should be stored in its original closed and weatherproof packaging at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from heat sources and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.

The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation.

Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.



Last edition: December 2023